

## DCW

### Air coolers (water)

Air cooler is mounted on the outside of the unit.


Casing of the cooler section corresponds to the unit's casing: galvanized steel sheets with internal mineral wool insulation of 45 mm thickness.

Cooler section is assembled with a drop separator and a drain tray.

Cooler control function is provided in the automatic control system of the unit.

Water 7/12°C.

Air temperature in/out – 30/18°C.



Type	Supply air volume, m³/h	Capacity, kW	Air pressure drop, Pa*	Fluid pressure loss, kPa	BxHxL, mm	B1xH1, mm	Tubes connections	Weight, kg	Connection side	Code
DCW-0,2-1	200	1,3	10	13	450x400x390	300x200	1/2"	27	R	1003882
									L	1009626
DCW-0,4-3	400	2,6	21	25	505x550x390	300x400	1/2"	33	R	765300001
									L	765300031
DCW-0,5-3	500	3,3	18	46	600x550x390	400x300	1/2"	35	R	765300063
									L	765300058
DCW-0,7-5	700	4,5	17	15	705x610x390	500x400	1/2"	42	R	765300003
									L	765300033
DCW-0,9-6	900	5,5	23	5	705x610x390	500x400	3/4"	45	R	765300005
									L	765300035
DCW-1,2-8	1200	7,4	38	10	705x610x420	500x400	3/4"	45	R	765300007
									L	765300037
DCW-1,4-9	1400	8,7	50	13	705x610x390	500x400	3/4"	45	R	765300029
									L	765300030
DCW-1,6-11	1600	10,0	54	18	755x610x420	500x400	3/4"	46	R	765300009
									L	765300039
DCW-2,0-13	2000	12,8	50	32	920x610x420	700x400	3/4"	57	R	765300025
									L	765300041
DCW-2,5-17	2500	15,5	63	13	1080x670x420	800x400	1"	65	R	765300013
									L	765300043
DCW-3,0-20	3000	18,7	88	18	1080x670x420	800x400	1"	65	R	765300015
									L	765300045
DCW-4,0-27	4000	25,2	92	32	1220x730x420	900x500	1"	82	R	765300017
									L	765300047
DCW-4,5-30	4500	28,8	94	55	1220x790x420	900x600	1"	87	R	765300019
									L	765300049
DCW-7,0-47	7000	44,4	89	29	1500x790x420	1200x600	1 1/2"	105	R	765300053
									L	765300054