

HCF F400

Axial smoke exhaust fan

Fans are designed for smoke exhaust 400 °C / 2H.

Made of galvanized steel, housing covered with epoxy paint.

motor meets the IP 55 protection class, insulation class – F.

Voltage 400 V.



Model	Maximum air flow, m3/h	Max. current consumption, A	Power consumption, W	Weight, kg
HCF 45 T4 0,75kW (A5:6) F400	6650	2,0	0,75	24,0
HCF 50 T4 0,75kW (A5:6) F400	8760	2,0	0,75	33,0
HCF 56 T4 0,75kW (A5:6) F400	10270	2,0	0,75	63,0
HCF 56 T4 1,1kW (A5:6) F400	11890	2,7	1,1	68,0
HCF 56 T4 1,5kW (A5:6) F400	13870	3,6	1,5	69,0
HCF 63 T4 0,75kW (A5:6) F400	11420	2,0	0,75	60,0
HCF 63 T4 1,1kW (A5:6) F400	14010	2,7	1,1	65,0
HCF 63 T4 1,5kW (A5:6) F400	15780	3,6	1,5	66,0
HCF 63 T4 2,2kW (A5:6) F400	17690	4,6	2,2	72,0
HCF 71 T4 0,75kW (A5:6) F400	12950	2,0	0,75	71,0
HCF 71 T4 1,1kW (A5:6) F400	15960	2,7	1,1	73,0
HCF 71 T4 1,5kW (A5:6) F400	18960	3,6	1,5	74,0
HCF 71 T4 2,2kW (A5:6) F400	22040	4,6	2,2	76,0
HCF 71 T4 3kW (A5:6) F400	23900	6,1	3,0	79,0
HCF 80 T4 3kW (A5:6) F400	28540	6,1	3,0	88,0
HCF 80 T4 4kW (A5:6) F400	32300	8,6	4,0	101,0
HCF 90 T4 11kW (A3:4) F400	46300	21,2	11,0	171,0
HCF 90 T4 11kW (A3:8) F400	47600	21,2	11,0	172,0
HCF 90 T4 15kW (A3:8) F400	52600	28,7	15,0	200,0
HCF 90 T4 3kW (A3:4) F400	27600	6,1	3,0	101,0
HCF 90 T4 4kW (A3:4) F400	32700	8,6	4,0	114,0
HCF 90 T4 5,5kW (A3:4) F400	39500	10,6	5,5	127,0
HCF 90 T4 5,5kW (A3:8) F400	32000	10,6	5,5	131,0
HCF 90 T4 7,5kW (A3:4) F400	44600	14,5	7,5	141,0
HCF 90 T4 7,5kW (A3:8) F400	37100	14,5	7,5	145,0
HCF 100 T4 11kW (A3:4) F400	62300	21,2	11,0	180,0
HCF 100 T4 11kW (A3:8) F400	52500	21,2	11,0	183,0
HCF 100 T4 15kW (A3:4) F400	65200	28,7	15	208,0

Modelis	Maksimalus oro kiekis, m ³ /h	Naudojama srovė, A	Galia, kW	Masė, kg
HCF 100 T4 15kW (A3:8) F400	63600	28,7	15	211,0
HCF 100 T4 18,5kW (A3:8) F400	71300	35,1	18,5	259,0
HCF 100 T4 22kW (A3:8) F400	75100	40,5	22	260,0
HCF 100 T4 5,5kW (A3:4) F400	45600	10,6	5,5	139,0
HCF 100 T4 7,5kW (A3:4) F400	51400	14,5	7,5	153,0
HCF 100 T4 7,5kW (A3:8) F400	39400	14,5	7,5	156,0
HCF 112 T4 11kW (A3:8) F400	75500	21,2	11	200,0
HCF 112 T4 11kW (A3:8) F400	57600	21,2	11	203,0
HCF 112 T4 15kW (A3:4) F400	86200	28,7	15	225,0
HCF 112 T4 15kW (A3:8) F400	72400	28,7	15	229,0
HCF 112 T4 18,5kW (A3:4) F400	89500	35,1	18,5	268,0
HCF 112 T4 18,5kW (A3:8) F400	82400	35,1	18,5	272,0
HCF 112 T4 22kW (A3:8) F400	91800	40,5	22	273,0
HCF 112 T4 30kW (A3:8) F400	99700	56,2	30	327,0
HCF 112 T4 5,5kW (A3:4) F400	50600	10,6	5,5	170,0
HCF 112 T4 7,5kW (A3:4) F400	59100	14,5	7,5	176,0
HCF 125 T4 11kW (A3:4) F400	74100	21,2	11	209,0
HCF 125 T4 15kW (A3:4) F400	91200	28,7	15	237,0
HCF 125 T4 18,5kW (A3:4) F400	102000	35,1	18,5	285,0
HCF 125 T4 18,5kW (A3:8) F400	77800	35,1	18,5	293,0
HCF 125 T4 22kW (A3:4) F400	112000	40,5	22	286,0
HCF 125 T4 22kW (A3:8) F400	91200	40,5	22	294,0
HCF 125 T4 30kW (A3:4) F400	121000	56,2	30	346,0
HCF 125 T4 30kW (A3:8) F400	111000	56,2	30	354,0
HCF 125 T4 37kW (A3:8) F400	124000	66,6	37	455,0
HCF 125 T4 45kW (A3:8) F400	135000	80,7	45	500,0

ORDER EXAMPLE: fan HCF 45 T4 0,75kW (A5:6) F400.