

RV, RT

Transformer fan speed controllers

5 steps motor rotation speed controller, ON/OFF switch. Controllers with thermo protection (except RV-0.6B).

RV- IP54,

RT-1.0...RT-5.0- IP54,

RT-7.0...RT-14.0- IP44.

Maximum ambient temperature 40 °C.



Model		Current, A	Code	Weight, kg
1 × 230V	RV-0.6B	0,6	742100148	1,0
	RV-1.2	1,2	742100044	1,7
	RV-1.5	1,5	742100061	1,8
	RV-2.2	2,2	742100029	2,4
	RV-3.0	3,0	742100051	3,1
	RV-4.0	4,0	742100048	3,7
	RV-5.0	5,0	742100050	4,2
	RV-7.0	7,0	742100055	6,5
	RV-11.0	11,0	742100049	8,2
	RV-14.0	14,0	742100054	10,7
3 × 400V	RT-1.0	1,0	742100141	6,0
	RT-2.0	2,0	742100142	7,8
	RT-3.0	3,0	742100043	10,3
	RT-4.0	4,0	742100144	14,2
	RT-5.0	5,0	742100031	18,0
	RT-7.0	7,0	742100033	23,0
	RT-11.0	11,0	742100145	33,0
	RT-14.0	14,0	742100034	36,0

ORDER EXAMPLE: speed controller RV-0.6B.