

TD-SILENT

Circular duct mounted tube fan

Fans TD-160...TD-1000 made of plastic. TD-1300...TD-2000 models housing are metal, coated with epoxypolyester paint, acoustically insulated.

The TD-T series fans are adjustable with a timer (1–30 minutes).

Technological highlights:

- adjustable speeds (except TD SILENT T),
- with thermal protection,
- ball bearings increases the life span.



Model	Max. current consumption, A	Voltage, V	Power consumption, W	Code	Weight, kg
TD-160/100N SILENT	0,16	1~ 230	20	721049528	1,4
TD-250/100 SILENT	0,11	1~ 230	24	721020024	5,4
TD-350/125 SILENT	0,13	1~ 230	30	722050422	4,9
TD-500/160 SILENT	0,22	1~ 230	50	721000060	6,0
TD-800/200 SILENT	0,45	1~ 230	95	721020021	8,7
TD-1000/200 SILENT	0,50	1~ 230	120	721000067	8,7
TD-1300/250 SILENT	0,83	1~ 230	197	721000068	20,0
TD-2000/315 SILENT	1,3	1~ 230	297	357870258	25,0
TD-250/100 SILENT T	0,11	1~ 230	24	721000387	5,5
TD-350/125 SILENT T	0,13	1~ 230	30	721000377	5,0
TD-500/160 SILENT T	0,22	1~ 230	50	721000388	6,0
TD-800/200 SILENT T	0,45	1~ 230	95	721000405	8,5
TD-1000/200 SILENT T	0,50	1~ 230	120	1021799	8,5

3 steps switches	5 steps motor rotation speed controller
PJ-4	RV-0.6B
PJ-4	RV-0.6B
PJ-4	RV-0.6B
PJ-4	RV-0.6B
PJ-4	RV-0.6B
PJ-4	RV-1.2
PJ-4	RV-2.2

ORDER EXAMPLE: fan TD-160/100N SILENT.