

TD

Circular duct mounted tube fan

Fans TD-160...TD-800 housings made of hard reinforced plastic. TD-1000...TD-6000 models housing are metal, coated with epoxypolyester paint.

The TD-T series fans are adjustable with a timer (1–30 minutes).

Technological highlights:

- adjustable speeds (except TD-T),
- with thermal protection,
- ball bearings increases the life span.



Model	Max. current consumption, A	Voltage, V	Power consumption, W	Code	Weight, kg	3 steps switches	5 steps motor rotation speed controller
TD-160/100N SILENT	0,16	1~ 230	20	721049528	1,4	PJ-4	RV-0.6B
TD-250/100	0,11	1~ 230	24	357870242	2,0	PJ-4	RV-0.6B
TD-350/125	0,13	1~ 230	30	357870245	2,0	PJ-4	RV-0.6B
TD-500/160	0,22	1~ 230	50	357870250	2,7	PJ-4	RV-0.6B
TD-800/200	0,50	1~ 230	120	357870252	4,9	PJ-4	RV-0.6B
TD-1000/250	0,50	1~ 230	125	357870255	9,4	PJ-4	RV-0.6B
TD-1300/250	0,80	1~ 230	180	357870257	9,4	PJ-4	RV-1.2
TD-2000/315	1,2	1~ 230	255	357870259	14,0	PJ-4	RV-1.5
TD-4000/355	1,5	1~ 230	345	721020016	19,0		RV-2.2
TD-6000/400	3,0	1~ 230	665	357870260	26,0		RV-4.0
TD-4000/355 TRIF	0,75	1~ 230	345	721020022	19,0		RT-1.0
TD-6000/400 TRIF	2,1	1~ 230	650	721020023	26,0		RT-3.0
TD-160/100 NT SILENT	0,16	1~ 230	20	721049526	1,4		
TD-250/100 T	0,11	1~ 230	24	357870318	2,0		
TD-350/125 T	0,13	1~ 230	30	357870320	2,0		
TD-500/160 T	0,22	1~ 230	50	357870324	2,7		
TD-800/200 T	0,50	1~ 230	120	721020015	4,9		

ORDER EXAMPLE: fan TD-160/100N SILENT.