

## TRKT, TRKTN


### Y-piece

T-pieces are designed to connect different or same diameter circular ducts. TRT-D-d T-piece connects main line with secondary line in 90 degrees angle. TRT-45-D-d T-piece connects main line with secondary line in 45 degrees angle. TRKT-D-d is used when main line is splitted into two separate lines. T-piece units are made from galvanized sheet metal with insertable connections to duct.

On demand:

TRTN-D-d, TRTN-45-D-d, TRKTN-D-d can be made from AISI-304 or AISI-316 stainless steel.

TRTC-D-d, TRTC-45-D-d, TRKTC-D-d from galvanized sheet metal covered with powder coating for outdoor use.



Dimensions, mm					TRKT	
D-d	L <sub>1</sub>	L <sub>1B</sub>	L <sub>MB</sub>	L <sub>M</sub>	Code	Weight, kg
125-100	40	40	63	112	704634232	0,7
125-125	40	40	80	120	704649221	0,8
160-125	40	40	80	143	704600014	1,1
200-160	40	40	100	244	704616217	1,3
250-200	40	40	120	300	704661194	1,9
315-250	40	40	145	370	704601204	2,8
355-250	40	65	150	370	704631963	2,9
400-315	40	65	183	461	704657581	6,3
450-315	40	65	183	461	704639833	6,5
500-355	65	65	203	522	704661195	8,2
560-400	65	65	250	655	704661196	12,0
630-450	65	65	250	655	704640142	13,0