


Verso R 1300 F C5

Nominal air flow according to ErP 2018, m ³ /h	1050
Nominal air flow according to ErP 2018, l/s	291,7
Electric air heater capacity, kW / Δt, °C	3/5,8
Supply voltage HE, V	3~400
Supply voltage HW, V	1~230
Maximal operating current HE, A	11,1
Maximal operating current HW, A	7,1
Power supply cable E, mm ²	5×1,5
Power supply cable W, mm ²	3×1,5
Electric power input of the fan drive at maximum flow rate, W	489
Noise power level, L _{WA} dB(A)	49
Noise pressure level, L _{PA} dB(A), (3 m)	38
Filters dimensions B×H×L, mm	410×420×46
Unit dimensions B×H×L, mm	940×480×1360
Panel thickness, mm	50
Maintenance space, mm	400
Unit weight, kg	144




Performance



Accessories

Closing damper	AGUJ-M-315+LF24/LM24
Silencer	ODA/EHA AGS-315-100-900-M
	SUP/ETA AGS-315-100-1200-M
Water heater	DH-315
PPU	PPU-HW-3R-15-1,0-W2
Water cooler	DCW-1,2-8
Water heater-cooler	DHCW-315
2-way valve	VVP47.15-2,5+SSF161.05HF
DX cooler	DCF-1,2-8
Cooling unit	MOU 24HFN8a+KA8140

Mounting positions



Temperature efficiency

	Winter					Summer		
Outside temperature, °C	-23	-15	-10	-5	0	25	30	35
After heat exchanger, °C	10,7	12,7	13,9	15,2	16,1	22,8	24	25,3

Indoor +22 °C, 20 % RH


Hot water duct air heater *

	Winter		
Water temperature in/out, °C	80/60	70/50	60/40
Capacity, kW	4	4	4
Flow rate, dm ³ /h	174	174	174
Pressure drop, kPa	5,4	5,5	5,6
Temperature in/out, °C	10,7 / 22,0		
Maximal capacity, kW	11,6	9,5	7,5
Connection, "	1/2		


* Option

Shown as right (R1)

View from inspection side



Shown as left (L1)



ODA – outdoor intake SUP – supply air ETA – extract indoor EHA – exhaust air